


Technical data sheet

OTICON | Opn

BTE13 PP (105)



	Oticon Opn 1	Oticon Opn 2	Oticon Opn 3
Speech Understanding			
OpenSound Navigator™	Level 1	Level 2	Level 3
- Balancing power effect	100%	50%	50%
- Max. noise removal	9 dB	5 dB	3 dB
Speech Guard™ LX	Level 1	Level 2	Level 3
Spatial Sound™ LX	4 estimators	2 estimators	2 estimators
Soft Speech Booster LX	•	•	•
Speech Rescue™ LX	•	•	•
Sound Quality			
Clear Dynamics	•	•	-
Binaural Noise Management	•	•	-
Fitting Bandwidth*	10 KHz	8 KHz	8 KHz
Processing Channels	64	48	48
Bass Boost (streaming)	•	•	•
Listening Comfort			
Transient Noise Management	4 configurations	On/Off	On/Off
Feedback shield LX	•	•	•
Wind Noise Management	•	•	•
YouMatic™ LX	3 configurations	2 configurations	1 configuration
Personalization & Optimizing Fitting			
Fitting Bands	16	14	12
Multiple Directionality Options	•	•	•
Adaptation Management	•	•	•
Oticon Firmware Updater	•	•	•
Fitting Formulas	VAC+, NAL-NL1 + 2, DSL v5.0	VAC+, NAL-NL1 + 2, DSL v5.0	VAC+, NAL-NL1 + 2, DSL v5.0
Connecting to the World			
Stereo streaming (2.4 GHz)	•	•	•
Oticon ON App	•	•	•
ConnectClip	•	•	•
Remote Control 3.0	•	•	•
TV Adapter 3.0	•	•	•
Tinnitus SoundSupport™	•	•	•
Expected battery life, hours**	80-105	80-105	80-105

* Bandwidth accessible for gain adjustments during fitting
** Battery size 13 - IEC PR41.

Real usage battery life is shown as an estimated interval based on mixed use cases with variable amplification settings and variable input levels, incl. direct stereo streaming from a TV (25% of the time) and streaming from a mobile phone (6% of the time).

Oticon Opn BTE13 PP features a compact design with a tactile double push button for easy operation of volume and programs. BTE13 PP comes with a telecoil and an optional discreet, two-color LED indicator to monitor hearing aid status.

OpenSound Navigator™ provides better speech understanding by continuously analyzing the environment, balancing all sound sources and attenuating the dominating noise.

TwinLink™ wireless technology combines binaural communication and 2.4 GHz connectivity in stereo directly to external digital devices with very low power consumption.

Fully programmable with updatable firmware, the Velox™ platform is ready for the future.

Oticon Opn is a Made for iPhone® hearing aid.

Oticon Opn is built on the new Velox platform, providing frequency resolution in 64 channels (Opn 1).



TwinLink
NFMI + 2.4 GHz

Made for

IP68

Oticon Opn is compatible with iPhone 7 Plus, iPhone 7, iPhone SE, iPhone 6s, iPhone 6s Plus, iPhone 6 Plus, iPhone 6, iPhone 5s, iPhone 5c, iPhone 5, 9.7-inch iPad Pro, 12.9-inch iPad Pro, iPad Air 2, iPad Air, iPad (4th generation), iPad mini 4, iPad mini 3, iPad mini 2, iPad mini, and iPod touch (5th and 6th generation). Devices must be running iOS 9.3 or later. Please visit www.oticon.com for more details on compatibility.

oticon
PEOPLE FIRST


Technical data			Ear Simulator			2CC Coupler			
			Measured according to IEC 60118-0:1983/AMD1:1994, IEC 60118-0:2015, IEC 60118-1:1995+AMD1:1998 CSV and IEC 60318-4:2010			ANSI S3.22-2014, IEC 60118-0:2015 and IEC 60318-5:2006			
Oticon Opn BTE13 PP			Opn 1	Opn 2	Opn 3	Opn 1	Opn 2	Opn 3	
Frequency range Hz			150-7300			120-7000			
OSPL90	Peak	138 (132*) dB SPL	131 (129*) dB SPL			123 (113*) dB SPL			
	1600 Hz	130 (121*) dB SPL	126 (118*) dB SPL			126 (118*) dB SPL			
	HFA-OSPL90	133 (126*) dB SPL							
Full-on gain**	Peak	73 (69*) dB	66 (66*) dB			57 (47*) dB			
	1600 Hz	65 (56*) dB	61 (54*) dB			61 (54*) dB			
	HFA-FOG	68 (62*) dB							
Reference test gain			57 dB			50 dB			
Telecoil output (1600 Hz)			1 mA/m field	97 dB SPL			-		
			10 mA/m field	117 dB SPL			-		
			SPLITS L/R	-			109/109 dB SPL		
Total harmonic distortion (Input 70 dB SPL)			500 Hz	7 %			3 %		
			800 Hz	5 %			<2 %		
			1600 Hz	<2 %			<2 %		
Equivalent input noise level			Omni	17 dB SPL			14 dB SPL		
			Dir	29 dB SPL			27 dB SPL		
Battery consumption***			Typical	1.8 mA			1.9 mA		
			Quiescent	1.6 mA			1.6 mA		
Battery life, artificial measurement, hours****			175			160			
IRIL (IEC 60118-13:2016)									

* For instruments fitted with Corda miniFit Power

** Measured with the gain control of the hearing aid set to its full-on position minus 20 dB and with an input SPL of 70 dB. This is to obtain a gain response equal to the full-on gain response from e.g. IEC 60118-0+A1:1994 but without influence of feedback.

*** Battery current is measured according to IEC 60118-0:1983/AMD1:1994 §7.11, IEC 60118-0:2015 §7.7 and ANSI S3.22:2014 §6.13 after a settling time of a minimum of 3 minutes.

**** Based on the standardized battery consumption measurement (IEC 60118-0:1983/AMD1:1994). The actual battery life depends on battery quality, use pattern, active feature set, hearing loss and sound environment.



Technical information: Omnidirectional mode is used unless otherwise stated.

Operating conditions

Temperature: +1°C to +40°C

Relative humidity:
5% to 93%, non-condensing

Storage and transportation conditions

Temperature and humidity should not exceed the following limits for extended periods during transportation and storage.

Temperature: -25°C to +60°C
Relative humidity: 5% to 93%, non-condensing

Instrument warning

The maximum output capability of the hearing instrument may exceed 132 dB SPL (IEC 711). Special care should be exercised in selecting and fitting the instrument as there may be risk of impairing the remaining hearing of the hearing instrument user.